

# L-PAD 10C

## 10 CHANNEL MIXING CONSOLE

### DESCRIPTION

With four transparent sound mic inputs, four stereo line inputs and the 2tk in/out, L-PAD10C is the ideal tool for duo/trio gigs, speech, background music diffusion, parties and all activities requiring several stereo inputs to be mixed. Two single-control compressors on mic channels help to handle even the more dynamic complex signals. The super versatile L-PAD slot permits the optional L-PAD MP3 PLAYER, PLAYER/RECORDER or BLUETOOTH CONNECTION cards to be inserted for even more flexible use. Thanks to the accurate Italian design L-PAD10C is easy to grab, transport and handle in all live situations. It is possible to install L-PAD10C on a mic stand thanks to the dedicated optional accessory or in a rack using the dedicated optional rack ears.



### FEATURES

- 4 mono INPUT + 4 stereo INPUT
- 2 Compressors (Ch. 1-2)
- 3band/2band EQ
- 1 AUX send
- External PSU 18V~ 1000mA

**TECHNICAL SPECIFICATIONS**

**Electronic specifications**                      Frequency Response:                      10 Hz ÷ 55000 kHz

---

**Inputs**

|                       |                |
|-----------------------|----------------|
| Mic:                  | 4              |
| Gain Range:           | 0 dB ÷ -50 dB  |
| Mic Inputs Impedance: | 2 kohm         |
| Low Cut:              | 75 Hz          |
| Phantom Power +48V:   | Yes            |
| Mono Line:            | 6              |
| Gain Selection:       | 15 dB ÷ -35 dB |
| Line Input Impedance: | 10 kohm        |

---

**Outputs**

|               |     |
|---------------|-----|
| Main MIX:     | 1   |
| Control Room: | Yes |
| AUX Send:     | 1   |
| AUX Output:   | 1   |
| Phones:       | 1   |
| 2 Track:      | Yes |

---

**Outputs specifications**

|                          |         |
|--------------------------|---------|
| Main Out Impedance:      | 120 ohm |
| Main Out Level:          | 22 dBu  |
| Aux Out Impedance (ohm): | 120 ohm |
| Aux Out Level:           | 22 dBu  |

---

**Compressors**                      RCF Compressors:                      On input 1 -2

---

**EQ**                      Input Channels EQ:                      2 Shelving 3

---

**Auxiliary sends**                      AUX:                      1 POST

---

**Electrical specifications**

|                          |               |
|--------------------------|---------------|
| Power supply:            | External      |
| Voltage requirements:    | 100 V - 240 V |
| Power consumption (MAX): | 24 W          |

---



|                                |                        |                       |
|--------------------------------|------------------------|-----------------------|
| <b>Standard compliance</b>     | CE marking:            | Yes                   |
| <b>Physical specifications</b> | Cabinet/Case Material: | ABS                   |
| <b>Size</b>                    | Height:                | 16 mm / 0.63 inches   |
|                                | Width:                 | 257 mm / 10.12 inches |
|                                | Depth:                 | 387 mm / 15.24 inches |
|                                | Weight:                | 2.65 kg / 5.84 lbs    |
| <b>Shipping informations</b>   | Package Height:        | 150 mm / 5.91 inches  |
|                                | Package Width:         | 510 mm / 20.08 inches |
|                                | Package Depth:         | 310 mm / 12.2 inches  |
|                                | Package Weight:        | 3.36 kg / 7.41 lbs    |

**PART NUMBER**

- **17140060**  
L-PAD 10C  
240V, UK  
EAN 8024530011574
  - **17140039**  
L-PAD 10C  
115V, US  
EAN 8024530011192
- **17140043**  
L-PAD 10C  
240V, AU  
EAN 8024530011406
  - **17140032**  
L-PAD 10C  
220-240V, EU  
EAN 8024530011208
- **17140042**  
L-PAD 10C  
100V, JP  
EAN 8024530011390